


SYMMETRIC ANTENNA WITH MULTI-MODE FUNCTIONALITY

4G LTE-M 824-960 MHz | 1710-2690 MHz

© We support frequency customization.

Clearance Area: 18 x 52 mm

Dimensions: 14.5 x 5.6 x 4.3 mm (Tolerance: ± 0.15 mm)



Model: ADCH001

PN: M01-X21506UWB5





Table of Contents

1 FEATURES & BENEFITS	1
2 APPLICATIONS.....	1
3 ORDER INFORMATION.....	1
4 MECHANICAL DIMENSIONS.....	2
5 REFERENCE GUIDE	3
6 EVALUATION BOARD WITH THE ANTENNA	3
7 MATCHING NETWORK.....	4
8 RECOMMENDED LAYOUT.....	5
9 ELECTRICAL PERFORMANCE	6
9.1 VSWR and Return Loss (dB)	6
9.2 Gain (dBi) and Total Efficiency (%)	7
9.3 2D and 3D Radiation Patterns (824-960 MHz)	9
9.4 2D and 3D Radiation Patterns (1710-2170 MHz).....	10
9.5 2D and 3D Radiation Patterns (2300-2690 MHz).....	11
10 SOLDERING CONDITIONS.....	12
11 PACKAGING.....	12
11.1 Optimal Storage Conditions for Packaged Reels	12
11.2 Packagings and Dimensions (Unit: mm).....	13
12 ANTENNA CERTIFICATION	14
ABOOSTY WELCOME ALL ANTENNA OEM/ODM PROJECTS	15




1 FEATURES & BENEFITS

- Low Profile
- Light Weight
- Easy to Integrate
- Intended for SMD Mounting
- Reduced Cost and Time-to-Market

2 APPLICATIONS

- IoT Devices
- Smart Cities
- Smart Agriculture
- Consumer Tracking
- Smart Metering
- Smart Agriculture



Antenna Image

3 ORDER INFORMATION

Product Name	H1001 4G LTE/Cellular Symmetric Antenna with Multi-Mode Functionality
Model	ADCH001
Part Number	M01-X21506UWB5
Dimensions	14.5 x 5.6 x 4.3 mm
Weight	0.4g
Mounting	SMT
Packaging	Tape & Reel
MOQ	1000 pcs/reel


[illegible]

5 REFERENCE GUIDE


Technical Features	824-960 MHz	1710-2690 MHz
Max VSWR	4.12 : 1	2.32 : 1
Max Efficiency	71.96%	
Max Return Loss	-4.31 dB	
Peak Gain	Up to 2.36 dBi (Typ)	
Polarization	Linear	
Input Impedance	50 Ω	
Operating Temperature	-40°C to +85°C	
Relative Humidity	10 to 70%	
All data were measured in free space and on a reference ground plane of 72 mm length, 52 mm width, and 1.6 mm thickness. Application data might vary.		

6 EVALUATION BOARD WITH THE ANTENNA

The evaluation board provides operation at 698-960, 1710-2690 MHz.
Evaluation Board dimension: 72 x 52 x 1.6 mm



Top View




Back View


Clearance Area: 18.0 x 52.0 mm



7 MATCHING NETWORK



It's strongly recommended to place the antenna near the edge of the board. Maximum antenna performance is achieved by placing the antenna towards one of the corners of the PCB and with the feed point of the antenna as close to same corner of the PCB as possible.



The technical drawing consists of two parts:


- Top View (Left):** A large rectangle containing a grid of small circles. Dimensions include a total width of 72.15, a distance from the left edge to the start of a feature of 40.56, and a vertical offset of 2.05. A U-shaped feature is shown near the bottom-left corner.
- Top View (Right):** A smaller rectangle with a grid of small circles. Dimensions include a total width of 41.36 and a vertical offset of 2.86.
- Side View (Bottom):** A long, thin horizontal rectangle with a total length of 52.87 and a thickness of 1.60.

9 ELECTRICAL PERFORMANCE


© Note

The data displayed in Chapter 10 were measured in free space and on a reference ground plane of 72mm length, 52 mm width, and 1.6 mm thickness.

9.1 VSWR and Return Loss (dB)



9.2 Gain (dBi) and Total Efficiency (%)





Antenna Data					
Freq (MHz)	Gain (dBi)	Efficiency (%)	Freq (MHz)	Gain (dBi)	Efficiency (%)
824	-1.59	37.8	904	-1.00	48.0
834	-1.60	39.1	914	-1.45	43.4
844	-1.12	42.4	924	-1.60	40.1
854	-0.87	46.3	934	-1.94	36.9
864	-0.90	47.4	944	-2.27	32.8
874	-0.51	49.4	954	-2.55	29.9
884	-0.99	49.8	960	-2.66	28.3
894	-1.06	48.6			



Freq (MHz)	Gain (dBi)	Efficiency (%)	Freq (MHz)	Gain (dBi)	Efficiency (%)
1710	1.54	65.4	2210	1.64	68.9
1730	1.90	68.0	2230	1.55	69.8
1750	2.04	69.8	2250	1.50	68.3
1770	2.04	70.5	2270	1.50	66.6
1790	2.22	70.9	2290	1.63	66.1
1810	2.36	70.4	2310	1.49	62.4
1830	2.29	72.0	2330	1.03	57.8
1850	2.24	71.7	2350	0.37	48.2
1870	2.21	70.7	2370	0.08	44.4
1890	2.25	69.6	2390	0.49	49.0
1910	2.18	68.8	2410	1.18	54.8
1930	1.86	69.1	2430	1.73	60.6
1950	2.04	71.6	2450	1.95	65.9
1970	1.98	71.4	2470	2.14	67.6
1990	1.83	68.8	2490	2.19	69.6
2010	1.48	63.2	2510	2.03	69.8
2030	0.41	51.1	2530	2.24	69.3
2050	-0.18	42.7	2550	2.16	66.5
2070	0.42	48.5	2570	1.86	60.7
2090	0.93	54.4	2590	1.85	61.0
2110	1.28	59.7	2610	2.09	63.5
2130	1.60	63.4	2630	2.07	64.7
2150	1.86	65.8	2650	2.08	65.1
2170	1.87	67.2	2670	2.20	63.8
2190	1.86	68.8	2690	2.36	63.2





9.3 2D and 3D Radiation Patterns (824-960 MHz)



@ 894MHz, Gain=-1.06 dBi





9.4 2D and 3D Radiation Patterns (1710-2170 MHz)



@ 1950MHz, Gain=2.04dBi



9.5 2D and 3D Radiation Patterns (2300-2690 MHz)




@ 2510MHz, Gain=2.03 dBi

10 SOLDERING CONDITIONS

This antenna is suitable for lead free soldering.

The reflow duration should be adjusted to create good solder joints without raising the antenna temperature beyond the allowed maximum of 260°C.

The figure below shows the temperature profile for soldering.



11 PACKAGING

11.1 Optimal Storage Conditions for Packaged Reels


Temperature	-5°C to 40°C
Humidity	Less than 70% RH
Shelf life	18 months
Storage place	Away from corrosive gas and direct sunlight
Packaging	Reels should be stored in unopened sealed manufacturer's plastic packaging.

© Note

Storage of open reels of antennas is not recommended due to possible oxidation of pads on antennas. If short-term storage is necessary, then it is highly recommended that the bag containing the antenna reel is re-sealed and stored in like storage conditions as in the above table.



11.2 Packagings and Dimensions (Unit: mm)





12 ANTENNA CERTIFICATION

RoHS Approval	Compliant [2011/65/EU&2015/863]
REACH Approval	Conform or declared [(EC)1907/2006]
Hazardous material regulation conformance: A certificate of conformance is available upon request. Feel free to consult us for details.	

 Global Site: www.aboosty.com  China Site: www.aboosty.cn

The materials provided herein, which are intended for illustration purposes only, are believed to be reliable and correct. However, no responsibility is further assumed for inaccuracies or incompleteness, and all such information shall be entirely at the user's risk. All information is subject to change without prior notice.

Copyright © 2025 ShenZhen MyAntenna RF Technology Co., Ltd. All Rights Reserved.
Aboosty™ is owned by Shenzhen MyAntenna RF Technology Co., Ltd. (often abbreviated as MyAntenna).



ABOOSTY WELCOME ALL ANTENNA OEM/ODM PROJECTS

Why Choose ABOOSTY



10+ years in antenna R&D, production, and OEM/ODM



MES system supported factory; 50M+ units annual output capacity



Factory directly competitive price



Quick price and lead time estimate



Innovative and patented design solutions




Professional team support & prompt reply within 24h

What We Provide


OEM/ODM Services	Light Customization	Deep Customization
	• Logo • Packaging • Cables & Connectors	• In-depth tailoring for specific applications • Functional enhancements • Environmental adaptations • Vertical certifications • ...

Custom Process

Light Customization Process



Deep Customization Process



Note: You can let us handle the PCB prototyping or do it yourself. Choosing self-prototyping may add 2 to 5 weeks to the timeline.

Boost Your Signal
with Our Antennas

ABOOSTY

A Globally Leading Manufacturer and Supplier of
Multi-band Combination Antennas

Contact us:

✉ support@aboosty.com

☎ +86-13924678201

Find us (Global):

🌐 www.aboosty.com

Search to follow us or to get technical support.



@Aboosty



Aboosty Antenna



Or click here to reach us directly.



🌐 国内官网: www.aboosty.cn



微信扫一扫以获取技术支持
Scan with WeChat App



微信扫一扫关注公众号
Scan with WeChat App